

STORAGETEK LTO TAPE DRIVES

VALUE WHERE IT COUNTS

KEY FEATURES

- **Cost-effective capacity.** Store up to 2.5 TB of native data on a single cartridge, reducing media costs while accommodating data growth.
- **Reduced backup windows.** Accelerate backups by processing more information in less time. The StorageTek LTO 6 tape drive moves data at rates as high as 160 megabytes per second, uncompressed.
- **Enhanced data protection.** Protect data integrity and help prevent data loss with powerful correction and verification capabilities.
- **WORM-capable media integration.** Secure, manage, and archive critical data records using WORM-capable media and StorageTek LTO 5 and StorageTek LTO 6 tape drives.
- **Encryption capability.** Encrypt data on the tape cartridge via the drive's built-in data encryption capability, and, in the event of tape cartridge loss, data is still protected.
- **Supports media partitioning.** The StorageTek LTO 5 and StorageTek LTO 6 specifications support two media partitions to allow for faster data access.



Today's continuous business environment requires that you back up more data in less time. Oracle's StorageTek LTO tape drives offer an economical, high-performance option for midrange tape automation environments.

Store, Manage, and Protect Growing Data

StorageTek LTO tape drives feature fast data transfer rates and large capacity so you can process more data in less time. The high-speed Fibre Channel interface further improves data movement, shortens backup windows, reduces downtime, and speeds recovery. Combined with StorageTek tape libraries, you can easily and affordably store, manage, and protect your growing data.

Oracle offers StorageTek LTO 6 tape drives in SAS or FC interfaces, full- and half-height platforms, and as single drives or within an automation environment. You choose the model that makes the most sense for your operating environment, application, capacity, and performance. The Fibre Channel interface available in automation products allows connections to new or existing SANs. Oracle's scalable tape automation solutions are designed to accommodate whatever drive and interface you choose.

Protect Your Investment with a Solid Upgrade Path

StorageTek LTO tape drives support two-generation backward compatibility so you can make the most of your technology investment. Their open format supports a wide variety of media suppliers and automation systems. And the LTO Compliance Verification Entity, an independent company, verifies interchange across LTO vendors and product generations.

Simplify Storage Management

Oracle's StorageTek LTO tape drives are compatible with leading backup and management software and hardware platforms, helping you to stretch your infrastructure investment. Choose StorageTek LTO Ultrium tape cartridges to accompany your tape purchase. All of our media is thoroughly tested for intercompatibility between applicable drives and StorageTek libraries.

Engage the Storage Experts

Oracle service professionals help you address storage challenges by delivering integrated services and solutions that optimize and manage storage performance over the life of your data. Our recognized, world-class service and customer care give you confidence that your technology investment is protected and that your business will be responsive to change. Oracle's storage service professionals can help you gain and sustain measurable results with the reliability and flexibility that you require. In addition, you can make your storage solution decisions even stronger with one of the largest selections of high-performance tape media in the industry.

| StorageTek LTO Tape Drive Specifications | | | | |
|---|--|--|--|--|
| Performance | StorageTek LTO 6 Half-Height | StorageTek LTO 6 Full-Height | StorageTek LTO 5 Half-Height | StorageTek LTO 5 Full-Height |
| Tape load and thread to ready | 24 sec | 22 sec | 19 sec | 19 sec |
| Average file access time (first file) | 50 sec | 50 sec | 52 sec | 52 sec |
| Maximum/average rewind time | 98/51 sec | 98/51 sec | 96/48 sec | 96/48 sec |
| Unload time (RW cartridge) | 19 sec | 19 sec | 19 sec | 19 sec |
| Unload time (WORM cartridge) | 23 sec | 22 sec | 23 sec | 22 sec |
| Data transfer rate, native (uncompressed) | 160 MB/sec | 160 MB/sec | 140 MB/sec | 140 MB/sec |
| Capacity | | | | |
| Capacity, native (uncompressed) | 2.5 TB | 2.5 TB | 1.5 TB | 1.5 TB |
| Capacity, native (compressed) | 6.25 TB (2.5:1) | 6.25 TB (2.5:1) | 3.0 TB (2:1) | 3.0 TB (2:1) |
| Availability | | | | |
| Mean time between failures (MTBF) Power on | 250,000 hrs @ 100% duty cycle | 250,000 hrs @ 100% duty cycle | 250,000 hrs @ 100% duty cycle | 250,000 hrs @ 100% duty cycle |
| Head life | 60,000 hrs | 60,000 hrs | 60,000 hrs | 60,000 hrs |
| Uncorrected bit error rate | 1x10 ⁻¹⁷ | 1x10 ⁻¹⁷ | 1x10 ⁻¹⁷ | 1x10 ⁻¹⁷ |
| Undetected bit error rate | 1x10 ⁻²⁷ | 1x10 ⁻²⁷ | 1x10 ⁻²⁷ | 1x10 ⁻²⁷ |
| Compatibility | | | | |
| Interface (SAS) | 6 Gb SAS | N/A | 6 Gb SAS | 6 Gb SAS |
| Burst transfer rate | 600 MB/sec | 600 MB/sec | 600 MB/sec | 600 MB/sec |
| Interface (Fibre Channel - automation only) | 8 Gb FC | 8 Gb FC | 8 Gb FC | 8 Gb FC |
| Read/write compatibility interface | LTO 6, LTO 5 read/write, LTO 4 (read only) | LTO 6, LTO 5 read/write, LTO 4 (read only) | LTO 5, LTO 4 read/write, LTO 3 (read only) | LTO 5, LTO 4 read/write, LTO 3 (read only) |
| Emulation modes | LTO 6 | LTO 6 | LTO 5 | LTO 5 |
| Mechanical | | | | |
| Desktop dimensions (W x H x D) | 8.86 x 3.11 x 11.73 (in.), 22.50 x 7.90 x 29.79 (cm) | N/A | 8.86 x 3.11 x 11.73 (in.), 22.50 x 7.90 x 29.79 (cm) | N/A |
| Desktop weight | 17.6 lb., 8.0 kg | N/A | 17.6 lb., 8.0 kg | N/A |
| Rackmount dimensions (W x H x D) | 19.0 x 1.75 x 25.25 (in.), 48.3 x 4.44 x 64.1 (cm) | N/A | 19.0 x 1.75 x 25.25 (in.), 48.3 x 4.44 x 64.1 (cm) | N/A |
| Rackmount weight | 21 lb., 9.52 kg | N/A | 21 lb., 9.52 kg | N/A |
| Automation dimensions (W x H x D) | 5.7 x 1.6 x 8.1 (in.), 14.47 x 4.06 x 20.57 (cm) | 5.7 x 3.3 x 8.2 (in.), 14.47 x 8.38 x 20.82 (cm) | 5.7 x 1.6 x 8.1 (in.) 14.47 x 4.1 x 20.82 (cm) | 5.7 x 3.3 x 8.2 (in.), 14.47 x 8.38 x 20.82 (cm) |
| Automation weight | 3.2 lb., 1.45 kg | 4.94 lb., 2.24 kg | 3.2 lb., 1.45 kg | 4.94 lb., 2.24 kg |
| Environmental | | | | |
| Temperature: operating | +50°F to +100°F (+10°C to +38°C) | +50°F to +100°F (+10°C to +38°C) | +50°F to +100°F (+10°C to +38°C) | +50°F to +100°F (+10°C to +38°C) |
| Temperature: nonoperating | -40°F to +140°F (-40°C to +66°C) | -40°F to +140°F (-40°C to +66°C) | -40°F to +140°F (-40°C to +66°C) | -40°F to +140°F (-40°C to +66°C) |
| Relative humidity: operating | 20% to 80% | 20% to 80% | 20% to 80% | 20% to 80% |

| | | | | |
|---------------------------------|--|---|--|---|
| Relative humidity: nonoperating | 10% to 95% | 10% to 95% | 10% to 95% | 10% to 95% |
| Power | | | | |
| Desktop | 100–240 V AC 50/60 Hz 0.7A max. Autoranging Power connection IEC 320 | N/A | 100–240 V AC 50/60 Hz 0.7A max. Autoranging Power connection IEC 320 | N/A |
| Rackmount | +5 V @ 3.5 A typical +12 V @ 1.0 A typical +5 V @ 4.5 A (max.) +12 V @ 2.0 A (max.) | N/A | +5 V @ 3.5 A typical +12 V @ 1.0 A typical +5 V @ 4.5 A (max.) +12 V @ 2.0 A (max.) | N/A |
| Automation | Varies depending on library configuration | Varies depending on library configuration | Varies depending on library configuration | Varies depending on library configuration |

Warranty

Visit oracle.com/us/support/policies/index.html#hardware for Oracle's global warranty support information on Oracle's StorageTek tape products.

Services

Visit oracle.com/us/support/index.html for information on Oracle's service program offerings for Oracle's StorageTek tape products.

Contact Us

For more information about Oracle's StorageTek LTO tape drives, please visit oracle.com/storage or call +1.800.786.0404 to speak to an Oracle representative.



Copyright © 2012, Oracle and/or its affiliates. All rights reserved.

This document is provided for information purposes only and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark licensed through X/Open Company, Ltd. 1212

Hardware and Software, Engineered to Work Together